


Conex | Bänninger

Series 8000

A range of Yellow Brass threaded fittings.



Features and Benefits:

- Yellow brass threaded fittings.
- Available in sizes 1/8-2".
- Manufactured to BSEN 1254-4.
- The threads are manufactured to ISO 228-1.
- Suitable to material with EN12165, CW617N, EN12164 and CW617N.

- Hydraulic working temperatures and pressures:

Size (inches)	Working pressure (bar)	
	-20°C to 120°C	> 120 to 225°C
1/4" to 3/4"	25	16
1 to 2	16	10
2 to 4	10	6



Conex | Bänninger

Series 8000

8000 Range

Brass Plug
Male Thread (Parallel)



8595
From: 1/4"
To: 2"

Female Elbow
Female x Female Thread



8090
From: 1/4"
To: 3/4"

Male x Female Elbow
Male x Female Thread



8092
From: 3/8"
To: 1"

Tee - Equal
Female Thread All Ends



8130
From: 1/4"
To: 1"

Reduced Bush
Male x Female Thread



8241
From: 3/8" x 1/4"
To: 2" x 1.1/2"

Straight Coupler
Female x Female Thread



8270
From: 1/4"
To: 2"

Hexagon Nipple
Male x Male Thread



8280
From: 1/8"
To: 2"

Flanged Backnut



8310
From: 1/2"
To: 2"

Barrel Nipple
Male Thread x Length(mm)



8530
From: 3/8" x 40mm
To: 2" x 100mm

Running Nipple
Male (Parallel)



8531
From: 1/4"
To: 3/4"

Blank Cap
Female Thread



8599
From: 1/4"
To: 2.1/2"



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: salesuk@ibpgroup.co.uk | Website: www.ibpgroup.com