


Geberit Mapress Stainless Steel T-piece, equal



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For saturated steam $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For treated water
- For rainwater with a pH value of > 6.0
- For grey and black water with pH value > 6.0
- For extinguishing water (wet)
- For sprinklers (wet)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Stainless Steel for liquid media
- Application overview – Geberit Mapress Stainless Steel for gaseous media

Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | CrNiMo steel 1.4401 (EN 10088)

Art. no.	DN	d, \varnothing	L	L1	I	Z	Z1
31009	65	76.1 mm	23 cm	11.0 cm	11.5 cm	6.2 cm	5.7 cm
31010	80	88.9 mm	26 cm	12.7 cm	13 cm	7 cm	6.7 cm
33008	10	12 mm	5.6 cm	3.5 cm	2.8 cm	1.1 cm	1.8 cm
31002	12	15 mm	6.4 cm	3.9 cm	3.2 cm	1.2 cm	1.9 cm
31003	15	18 mm	6.8 cm	4.1 cm	3.4 cm	1.4 cm	2.1 cm
31004	20	22 mm	7.4 cm	4.4 cm	3.7 cm	1.6 cm	2.3 cm
31005	25	28 mm	8.4 cm	5 cm	4.2 cm	1.9 cm	2.7 cm
31006	32	35 mm	10 cm	5.7 cm	5 cm	2.4 cm	3.1 cm
31007	40	42 mm	11.4 cm	6.5 cm	5.7 cm	2.7 cm	3.5 cm
31008	50	54 mm	13.8 cm	7.7 cm	6.9 cm	3.4 cm	4.2 cm
31011	100	108 mm	31 cm	15.3 cm	15.5 cm	8 cm	7.8 cm