


Geberit Mapress Copper bend



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	arc	L	Z
60101	10	12 mm	90 °	3.1 cm	1.4 cm
60601	10	12 mm	45 °	2.6 cm	0.9 cm
60602	12	15 mm	45 °	3.6 cm	1.6 cm
60102	12	15 mm	90 °	3.8 cm	1.8 cm
60603	15	18 mm	45 °	2.9 cm	0.9 cm
60103	15	18 mm	90 °	4.2 cm	2.2 cm
60604	20	22 mm	45 °	3.2 cm	1.1 cm
60104	20	22 mm	90 °	4.7 cm	2.6 cm
60605	25	28 mm	45 °	3.7 cm	1.4 cm
60105	25	28 mm	90 °	5.7 cm	3.4 cm
60606	32	35 mm	45 °	4 cm	1.4 cm
60106	32	35 mm	90 °	6.5 cm	3.9 cm
60607	40	42 mm	45 °	4.7 cm	1.7 cm
60107	40	42 mm	90 °	7.6 cm	4.6 cm
60608	50	54 mm	45 °	5.7 cm	2.2 cm
60108	50	54 mm	90 °	9.5 cm	6 cm



- In 2020, the dimensions of bend d15/45° will be modified. The new dimensions are listed in the overview "Dimensional changes for Geberit Mapress Copper 2020".