


Geberit Mapress Copper bend with plain end



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of CIIR, black, up to $\varnothing \leq 54\text{ mm}$
- Seal ring made of EPDM, black, from $\varnothing > 54\text{ mm}$
- Pressing socket with transparent protection plug

Technical data

Product material | Cu-DHP copper CW024A (EN 1412)

Art. no.	DN	d, \varnothing	arc	L	H	Z
60301	10	12 mm	90 °	3.1 cm	4.5 cm	1.4 cm
60701	10	12 mm	45 °	2.6 cm	3.5 cm	0.9 cm
60702	12	15 mm	45 °	3.6 cm	4.5 cm	1.6 cm
60302	12	15 mm	90 °	3.8 cm	5.1 cm	1.8 cm
60703	15	18 mm	45 °	2.9 cm	3.9 cm	0.9 cm
60303	15	18 mm	90 °	4.2 cm	5.3 cm	2.2 cm
60704	20	22 mm	45 °	3.2 cm	4.4 cm	1.1 cm
60304	20	22 mm	90 °	4.7 cm	6 cm	2.6 cm
60705	25	28 mm	45 °	3.7 cm	4.5 cm	1.2 cm
60305	25	28 mm	90 °	5.7 cm	6.5 cm	3.4 cm
60706	32	35 mm	45 °	4 cm	4.9 cm	1.4 cm
60306	32	35 mm	90 °	6.5 cm	7.4 cm	3.9 cm
60707	40	42 mm	45 °	4.7 cm	5.7 cm	1.7 cm
60307	40	42 mm	90 °	7.6 cm	8.6 cm	4.6 cm
60708	50	54 mm	45 °	5.7 cm	6.8 cm	2.2 cm
60308	50	54 mm	90 °	9.5 cm	10.6 cm	6 cm



- In 2020, the dimensions of bend d15/45° will be modified. The new dimensions are listed in the overview "Dimensional changes for Geberit Mapress Copper 2020".