


Geberit Mapress Copper adapter socket



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water ≤ 120 °C
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For connecting copper pipe diameters alien to the system
- For transitions from copper pipes to mild steel pipes
- For technical building systems, industry and shipbuilding

- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed
- ø 14 mm to be pressed with Geberit Mapress pressing jaw ø 15 mm
- ø 16 mm should be pressed with the Geberit Mapress pressing jaw ø 18 mm
- Seal ring made of CIIR, black
- O-ring made of EPDM
- Pressing socket with transparent protection plug

Technical data

Product material | Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, ø	d1, ø	L	Z
62020	12	15 mm	14 mm	4.1 cm	0.1 cm
62022	12	15 mm	16 mm	4.1 cm	0.1 cm
62024	15	18 mm	16 mm	4.1 cm	0.1 cm