


Geberit Mapress Copper adapter union with female thread



Example image



Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For compressed air (oil purity class 0–3)
- For negative pressure
- For inert gases (e.g. nitrogen)
- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Copper

Characteristics

- Pressing indicator
- Leaky if unpressed
- Union nut made of brass
- Seal ring made of CIIR, black
- Flat gasket made of EPDM
- Pressing socket with transparent protection plug

Technical data

Media temperature with flat gasket EPDM	0–100 °C
Product material	Gunmetal (CuSn5Zn5Pb2-C)

Art. no.	DN	d, Ø	Rp	G	L	Z
65481	10 / 15	12 mm	1/2 "	1/2 "	5.2 cm	2.2 cm
65482	12 / 15	15 mm	1/2 "	3/4 "	5 cm	1.7 cm
65490	12 / 20	15 mm	3/4 "	3/4 "	5.9 cm	2.4 cm
65483	15	18 mm	1/2 "	3/4 "	5 cm	1.7 cm
65491	15 / 20	18 mm	3/4 "	3/4 "	5.9 cm	2.4 cm
65484	20	22 mm	3/4 "	1 "	6.2 cm	2.6 cm
65492	20 / 25	22 mm	1 "	1 "	6.6 cm	2.8 cm
65485	25	28 mm	1 "	1 1/4 "	6.3 cm	2.3 cm
65486	32	35 mm	1 1/4 "	1 1/2 "	7.5 cm	3 cm
65487	40	42 mm	1 1/2 "	1 3/4 "	7.9 cm	3 cm
65488	50	54 mm	2 "	2 3/8 "	8.5 cm	2.7 cm