


## Geberit Mapress Stainless Steel adapter with female thread



Example image



### Application purposes

- For cold and hot potable water
- For heating water
- For cooling water without antifreeze agent
- For cooling water with antifreeze agent
- For remote network heating water  $\leq 120\text{ }^{\circ}\text{C}$
- For saturated steam  $\leq 120\text{ }^{\circ}\text{C}$
- For service water
- For treated water
- For rainwater with a pH value of  $> 6.0$
- For grey and black water with pH value  $> 6.0$
- For extinguishing water (wet)
- For sprinklers (wet)
- For chemicals and technical liquids
- For compressed air (oil purity class 0–3)
- For negative pressure

- For inert gases (e.g. nitrogen)
- For industrial gases (e.g. acetylene, shielding gases)
- For technical building systems, industry and shipbuilding
- Application overview – Geberit Mapress Stainless Steel for liquid media
- Application overview – Geberit Mapress Stainless Steel for gaseous media

### Characteristics

- Pressing indicator
- Leaky if unpressed
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

### Technical data

Product material | CrNiMo steel 1.4401 (EN 10088)

Art. no.	DN	d, $\varnothing$	Rp	L	Z
33010	10 / 15	12 mm	1/2 "	3.4 cm	0.4 cm
31802	12 / 15	15 mm	1/2 "	3.7 cm	0.4 cm
31823	12 / 20	15 mm	3/4 "	3.8 cm	0.3 cm
31803	15	18 mm	1/2 "	3.7 cm	0.4 cm
31804	15 / 20	18 mm	3/4 "	3.8 cm	0.3 cm
31805	20 / 15	22 mm	1/2 "	3.6 cm	0.2 cm
31806	20	22 mm	3/4 "	3.9 cm	0.3 cm
31824	20 / 25	22 mm	1 "	4.2 cm	0.4 cm
31807	25 / 15	28 mm	1/2 "	3.8 cm	0.2 cm
31819	25 / 20	28 mm	3/4 "	3.9 cm	0.3 cm
31809	25	28 mm	1 "	4.4 cm	0.4 cm
31825	25 / 32	28 mm	1 1/4 "	4.6 cm	0.4 cm
31820	32 / 25	35 mm	1 "	4.5 cm	0.2 cm
31811	32	35 mm	1 1/4 "	4.9 cm	0.4 cm
31826	32 / 40	35 mm	1 1/2 "	4.9 cm	0.4 cm
31821	40 / 32	42 mm	1 1/4 "	5.1 cm	0.2 cm
31814	40	42 mm	1 1/2 "	5.3 cm	0.4 cm
31822	50 / 40	54 mm	1 1/2 "	7.1 cm	2.2 cm
31818	50	54 mm	2 "	6.2 cm	0.4 cm